

# ZCKD15

Limit switch head, Limit switches XC Standard, ZCKD, thermoplastic roller lever



## Main

|                            |   |
|----------------------------|---|
| Range of product           | Telemecanique Limit switches XC Standard  |
| Series name                | Standard format   |
| Product or component type  | Limit switch head   |
| Device short name          | ZCKD  |
| Head type                  | Rotary head   |
| Product compatibility      | XCKL<br>XCKM  |
| Associated body            | ZCKMD39<br>ZCKL1<br>ZCKLD31H7<br>ZCKLD35H7<br>ZCKMD35<br>ZCKM1H7<br>ZCKM5<br>ZCKM1H29<br>ZCKLD39H7<br>ZCKM8H29<br>ZCKL5<br>ZCKM1<br>ZCKM8H7<br>ZCKLD37H7<br>ZCKL7H7<br>ZCKM6H29<br>ZCKM9H29<br>ZCKM5H29<br>ZCKMD35H7<br>ZCKM8<br>ZCKMD37H7<br>ZCKL7<br>ZCKLD39<br>ZCKMD37<br>ZCKL8<br>ZCKMD31<br>ZCKLD31<br>ZCKL1H7<br>ZCKMD35H29<br>ZCKM7<br>ZCKM6H7<br>ZCKM6<br>ZCKL5H7<br>ZCKM9<br>ZCKL6<br>ZCKL6H7<br>ZCKM7H29<br>ZCKM5H7<br>ZCKMD31H7<br>ZCKM7H7<br>ZCKMD31H29<br>ZCKLD37<br>ZCKMD39H29<br>ZCKL8H7<br>ZCKMD39H7<br>ZCKMD37H29<br>ZCKLD35 |
| Movement of operating head | Rotary  |
| Type of operator           | Roller lever spring return thermoplastic  |
| Type of approach           | Lateral approach, 2 directions  |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither TWSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Complementary

|                  |            |
|------------------|------------|
| Switch actuation | By 30° cam |
| Positive opening | With       |
| Head material    | Metal      |

## Environment

|                                       |                      |
|---------------------------------------|----------------------|
| Ambient air temperature for operation | -25...70 °C          |
| Ambient air temperature for storage   | -40...70 °C          |
| Environmental characteristic          | Standard environment |

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 3.400 cm  |
| Package 1 Width              | 6.200 cm  |
| Package 1 Length             | 7.800 cm  |
| Package 1 Weight             | 90.000 g  |
| Unit Type of Package 2       | S01       |
| Number of Units in Package 2 | 28        |
| Package 2 Height             | 15.000 cm |
| Package 2 Width              | 15.000 cm |
| Package 2 Length             | 40.000 cm |
| Package 2 Weight             | 2.800 kg  |
| Unit Type of Package 3       | P06       |
| Number of Units in Package 3 | 896       |
| Package 3 Height             | 75.000 cm |
| Package 3 Width              | 60.000 cm |
| Package 3 Length             | 80.000 cm |
| Package 3 Weight             | 95.444 kg |

## Offer Sustainability

|  |   |
|--|---|
| Sustainable offer status                   | Green Premium product   |
| Circularity Profile                        | No need of specific recycling operations  |
| California proposition 65                  | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| For all Reach Rohs enquiries contact us at | <a href="mailto:sustainability@tesensors.com">sustainability@tesensors.com</a>  |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|